



**SUGGESTED SPECIFICATION VERBIAGE FOR
ZRC-221 COLD GALVANIZING COMPOUND**

Organic Zinc-Rich Coating containing a maximum of 221 gms/L VOC, as supplied, and at least 92% metallic zinc (ASTM D520, Type III), by weight, in the dried film, exhibiting galvanic, anti-corrosion protection to iron and steel, and conforming to Society for Protective Coatings Specification SSPC Paint 20, Type II, Level 1, Zinc Rich Coating and American Society for Testing and Materials Standard Practice for Repair of Damaged and Uncoated Areas of Hot-Dip Galvanized Coatings, ASTM A 780-01, and meeting the performance requirements of Specification SSPC Paint 29, Type II, Level 1, Zinc Dust Sacrificial Primer Performance-Based, Military Specification MIL-P-21035B, Paint High Zinc Dust Content, Galvanizing Repair (Metric) and Military Specification MIL-PRF-26915D, Primer Coating, For Steel Surfaces; as manufactured by ZRC Worldwide, Marshfield, MA or other facility having been registered to the International Organization for Standardization ISO 9000:2000 standard for quality.

**Please take advantage of our toll-free number 1-800-831-3275
To place an order or speak with a technical representative**

145 Enterprise Drive, Marshfield, MA 02050
Tel: 781-319-0400; Fax: 781-319-0404; E-mail: info@zrcworldwide.com
Web: www.zrcworldwide.com